



製品記号	ベルト巾	D2	l2	m2	n2	A	B	t	T	C	F	M	H	e × f	ベアリング	重量kg
OKVR-40	400	89.1	210	640	60	690	110	4.5	20	450	214	74	54	15×25	6204	12.3
OKVR-45	450		240	690		740				510	215	75	53			13.0
OKVR-50	500		270	740		790				216	76	51	13.7			
OKVR-60	600		320	840		890				218	78	49	15.1			
OKVR-75	750	114.3	415	1040	1090	857	246	69	32	23.0						
OKVR-90	900	490	1190	1240	1006	249	73	29	25.5							
OKVR-105	1050	139.8	565	1340	100	1390	150	6	25	1163	296	83	32	19×30	6205	38.5
OKVR-120	1200		640	1490		1540				311	86	29	46.7			
OKVR-140	1400	165.2	750	1730	120	1790	180	9	1530	358	108	41	65.7			
OKVR-160	1600		850	1930		1990			370	112	36	88.5				
OKVR-180	1800		980	2220		2290	395		116	29	100.7					
OKVR-200	2000		1080	2420		2490	400		121	25	109.1					

Product symbol	Belt width	D2	l 2	m2	n2	A	B	t	T	C	F	M	H	e × f	Ball bearing	Weight(kg)					
OKVR-40	400	89.1	210	640	60	690	110	4.5	20	450	214	74	54	15×25	6204	12.3					
OKVR-45	450		240	690		740				510	215	75	53			13.0					
OKVR-50	500		270	740		790				570	216	76	51			13.7					
OKVR-60	600		320	840		890				670	218	78	49			15.1					
OKVR-75	750	114.3	415	1040	100	1090	150	6	25	857	246	69	32		6205	23.0					
OKVR-90	900		490	1190		1240				1006	249	73	29			25.5					
OKVR-105	1050	139.8	565	1340	120	1390	180			25	25	1163	296			83	32	6206	38.5		
OKVR-120	1200		640	1490		1540						1313	311			86	29		46.7		
OKVR-140	1400	165.2	750	1730	120	1790	180					25	25	1530	358	108	41		19×30	6206	65.7
OKVR-160	1600		850	1930		1990								1729	370	112	36				88.5
OKVR-180	1800		980	2220		2290	1988			395	116			29	100.7						
OKVR-200	2000		1080	2420		2490	2187			400	121			25	109.1						